

.git*

git

- .git* - .gitattributes
- .git* - .gitignore

.gitconfig

- ~/.gitconfig:

```
[alias]
    ck = checkout
    s = status
    l = log --oneline --max-count=10
    ll = log --pretty=format:@"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate --numstat
    lg = log --oneline --decorate --graph
    ls = log --pretty=format:@"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate
    alias = ! git config --get-regexp ^alias\\. | sed -e s/^alias\\.\\.// -e s/\\
/\\ =\\ /
    a = add
    b = branch
    c = commit
    bv = branch -avv
    lv = log --walk-reflogs --max-count=10
    ai = add --interactive
    ss = status --short
```

<https://gist.github.com/johnpolacek/69604a1f6861129ef088>

```
[alias]
    co = checkout
    cob = checkout -b
    coo = !git fetch && git checkout
    br = branch
    brd = branch -d
    brD = branch -D
    merged = branch --merged
    st = status
    aa = add -A .
    cm = commit -m
    aacm = !git add -A . && git commit -m
    cp = cherry-pick
    amend = commit --amend -m
    dev = !git checkout dev && git pull origin dev
    staging = !git checkout staging && git pull origin staging
    master = !git checkout master && git pull origin
    po = push origin
    pod = push origin dev
    pos = push origin staging
    pom = push origin master
    poh = push origin HEAD
    pogm = !git push origin gh-pages && git checkout master && git pull origin
```

```
master && git rebase gh-pages && git push origin master && git checkout gh-pages
pomg = !git push origin master && git checkout gh-pages && git pull origin gh-
pages && git rebase master && git push origin gh-pages && git checkout master
plo = pull origin
plod = pull origin dev
plos = pull origin staging
plom = pull origin master
ploh = pull origin HEAD
unstage = reset --soft HEAD^
ls = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate
ll = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate --numstat
f = "!git ls-files | grep -i"
gr = grep -Ii
la = "!git config -l | grep alias | cut -c 7-"
```

.gitkeep

Fichero vacío para indicar que ese directorio se ha de mantener, aunque no contenga más archivos.

From:

<https://matebcn.eu/> - miguel angel torres egea

Permanent link:

<https://matebcn.eu/tech:git:dotfiles>

Last update: **13/07/2026 10:57**

